

## Screwdrivers with torque control - Clutch type:

### ACCU-TRK

STRAIGHT SCREWDRIVERS - Push start - AMI Series

WATT: 70

Hexagonal coupling: 1/4"

Data sheet



## Technical specification

## Screwdrivers with torque control - Clutch type:

### ACCU-TRK

STRAIGHT SCREWDRIVERS - Push start - AMI Series

WATT: 70

Hexagonal coupling: 1/4"

## Data sheet

|                          |          |
|--------------------------|----------|
| Model                    | AMI22AT  |
| Code                     | 8301052  |
| No-load speed - rpm/min  | 1200     |
| Screw tightening - Metal | M3 - M4  |
| Torque - Nm              | 0,4-1,8  |
| Spring colour            | Blue     |
| Length - mm              | 215      |
| Body - ø mm              | 33       |
| Air connection           | 1/8" GAS |
| Weight - Kg              | 0,5      |
| Hose - ø min mm          | 6        |
| Air consumption - NI/min | 300      |
| dB (A)                   | 70       |
|                          | AMI44AT  |
|                          | 8301054  |
|                          | 800      |
|                          | M4 - M5  |
|                          | 1,7-2,4  |
|                          | Neutral  |
|                          | 215      |
|                          | 33       |
|                          | 1/8" GAS |
|                          | 0,5      |
|                          | 6        |
|                          | 300      |
|                          | 70       |
|                          | AMI66AT  |
|                          | 8301056  |
|                          | 500      |
|                          | M4 - M5  |
|                          | 1,7-3,7  |
|                          | Neutral  |
|                          | 215      |
|                          | 33       |
|                          | 1/8" GAS |
|                          | 0,5      |
|                          | 6        |
|                          | 300      |

## Screwdrivers with torque control - Clutch type:

### ACCU-TRK

STRAIGHT SCREWDRIVERS - Push start - AMI Series

WATT: 70

Hexagonal coupling: 1/4"

Data sheet

## Overall dimensions

