

Screwdrivers - Clutch type: SLIP-TRK/RE

GUN SCREWDRIVERS - ERGOVIT series

WATT: 220

Hexagonal coupling : 1/4"

Data sheet
ERGOVIT55RE



Description

Slip clutch. Adjusting this type of clutch is easy; just turn the ring nut on the outside. This type is ideal where frequent changes of tightening torque within the spring range are required and where you need to maintain a high degree of precision.

Technical specification

Model	ERGOVIT55RE
Code	8302175
No-load speed - rpm/min	380
Screw tightening - Metal	8
Screw tightening - Wood	5,5x50
Torque - Nm	15,7
Spring colour - *	Neutral
Length - mm	223
Body - ø mm	38
Air connection	1/4"GAS
Weight - kg	1,3
Hose - ø min mm	8
Air consumption - NI/min	680

GUN SCREWDRIVERS - ERGOVIT series

Hexagonal coupling : 1/4"

ERGOVIT55RE

Technical drawing of a 1/2 inch impact wrench. The drawing shows the side profile of the tool with various dimensions in millimeters. The overall length is 223.2 mm. The dimensions are as follows:

- Overall length: 223.2 mm
- Section 1 length: 72.5 mm
- Section 2 length: 22.5 mm
- Section 3 length: 44.7 mm
- Section 4 length: 83.5 mm
- Section 5 length: 158 mm
- Section 6 length: 41 mm
- Section 7 length: 151 mm

The drawing also includes a detail view of the impact anvil, showing a diameter of 20 mm and a length of 28 mm. The impact anvil is labeled with the number 151.