SLOW MOTORS

LGG SERIES - Reversible

WATT: 400 / CONSUMPTION: 560 Nl/1'

Data measured at pressure of 6 bar - Minimum supply hose diameter: 8 mm

Data sheet
LGG200R



1. Cylindrical keyed shaft
2. Grip zone
3. Air inlets
4. Air exhaust


Technical specification

- Model	LGG200R
- Code	8731215
Speed rpm - No-load	200
Speed rpm - at Max Power	120
Torque Nm - at Max Power	33
Torque Nm - Stall Torque	47

Form features

The normal delivery condition of the models listed in the table is that with cylindrical shaft and cylindrical body as shown in the photo.

Characteristic curves





SLOW MOTORS

LGG SERIES - Reversible

WATT: 400 / CONSUMPTION: 560 Nl/1'

Data measured at pressure of 6 bar - Minimum supply hose diameter: 8 mm


Data sheet

LGG200R

Permissible radial and axial loads

Model	Code	Fr (N)	Fa (N)	Co (N)
LGG200	8731215	2100	2350	4750

Overall dimensions



Model	Code	A	B	C	D	E	F	G	H	I	J	K	L	U	V	W	X	Y	Z
LGG200R	8731215	203,5	29,5	48	42	81,5	31,5	14	3	5	5	22	M6	11	13	48	40	1/4"	3/8"