

MOTORS WITH POWER UP TO 850 W

LCYO SERIES - Reversible

WATT: 110 / CONSUMPTION: 340 NI/1'

Data measured at pressure of 6 bar - Minimum supply hose diameter: 5 mm

Data sheet
LCYO11R



1. Cylindrical keyed shaft
2. Grip zone
3. Air inlets
4. Air exhaust

Technical specification

- Model	LCYO11R
- Code	8731231
Speed rpm - No-load	4700
Speed rpm - at Max Power	2875
Torque Nm - at Max Power	0,4
Torque Nm - Stall Torque	0,6

Form features

Standard delivery condition:

cylindrical shaft and body as shown in the photo.

Optional:



Shaft - threaded - indication /AF (left rotation excluded - subject to checks for reversible)

- conical - indication /AC

- with collets - indication / AP

Flange or auxiliary supports

Characteristic curves



MOTORS WITH POWER UP TO 850 W

LCYO SERIES - Reversible

WATT: 110 / CONSUMPTION: 340 NI/1'


Data measured at pressure of 6 bar - Minimum supply hose diameter: 5 mm

Data sheet
LCYO11R

Permissible radial and axial loads

Model	Code	Fr (N)	Fa (N)	Co (N)
LCYO11	8731231	350	200	850

Overall dimensions



Model	Code	A	B	C	D	F	G	H	I	L	M	N	O	P	Q	S	S1
LCYO11R	8731231	113	21	26	30	30	10	2,5	4	M4	3/8"x24UNF	10	14	B10	19	ER11	16,5