


MOTORS FOR SCREW DRIVING APPLICATIONS WITH ACCU-TRK CLUTCH

ALGS ACCU-TRK SERIES - Reversible

WATT: 430 / CONSUMPTION: 600 NI/1"

The left rotation is not controlled by the friction clutch. On ATE version:
direct starting for Right and reversible motors.

Data sheet
ALGS3R ATE



- 1. 1/4" hexagonal bit holder
- 2. Grip zone
- 3. Compressed air inlet
- 4. Screwing completed signal

Technical specification

Reversible - Model	ALGS3R ATE
Reversible - Code	8604283
No-load speed - rpm/min	800
Torque Nm - Nm	2,0 - 7,6
Clutch spring	Silver

Form features

Standard coupling bit holder 1/4" (6.35 mm)

Torque Adjustment


MOTORS FOR SCREW DRIVING
APPLICATIONS WITH ACCU-TRK CLUTCH

Data sheet
ALGS3R ATE


ALGS ACCU-TRK SERIES - Reversible

WATT: 430 / CONSUMPTION: 600 NI/1"

The left rotation is not controlled by the friction clutch. On ATE version:
direct starting for Right and reversible motors.



Overall dimensions



MOTORS FOR SCREW DRIVING APPLICATIONS WITH ACCU-TRK CLUTCH

ALGS ACCU-TRK SERIES - Reversible

WATT: 430 / CONSUMPTION: 600 NI/1"

The left rotation is not controlled by the friction clutch. On ATE version:
direct starting for Right and reversible motors.

Model	Code	A	B	C	D	D1	D2	F	G	K	K1	S	T	Y	&
ALGS3R ATE	8604283	202,5	51,5	40	42	17	56	82	12	22	31	38	32	1/4"	65

Data sheet
ALGS3R ATE