

Screwdrivers - Clutch type: SLIP-TRK

GUN SCREWDRIVERS - SUPERGOVIT series

WATT: 440

Hexagonal coupling: 1/4"

Data sheet
SUPERGOVIT5



Description

Slip clutch. In this case the clutch is adjusted using the Allen keys provided. This solution is ideal for those situations where a simple system for adjusting the tightening torque is required. Various adjustment ranges can be obtained by simply changing the springs. Models for use in wider than standard ranges are supplied with an extra spring. In those cases where frequent changes to tightening torques are required, we recommend that you use a tool equipped with a series of clutch units each set to a particular torque; when you need to change torque setting, just change the clutch unit. When ordering, use the codes indicated in the table.

Technical specification

Screwdrivers - Clutch type: SLIP-TRK

GUN SCREWDRIVERS - SUPERGOVIT series

WATT: 440

Hexagonal coupling: 1/4"

Model	SUPERGOVIT5
Code	8302068
No-load speed - rpm/min	380
Screw tightening - Metal	10
Screw tightening - Wood	6x60
Torque - Nm	25
Spring colour - *	Red
Length - mm	215
Body - ø mm	44
Air connection	1/4"GAS
Weight - Kg	1,37
Hose - ø min mm	10
Air consumption - NI/min	750

Data sheet
SUPERGOVIT5

Overall dimensions

Screwdrivers - Clutch type: SLIP-TRK

GUN SCREWDRIVERS - SUPERGOVIT series

WATT: 440

Hexagonal coupling: 1/4"

Data sheet
SUPERGOVIT5

