Screwdrivers with torque control - Clutch type: ACCU-TRK

Data sheet
ERGOVIT20AT

GUN SCREWDRIVERS - Button /push start - ERGOVIT series
WATT: 220
Hexagonal coupling: 1/4”



Description

This clutch type stops the power supply to the motor and stops tool rotation when a preset torque is reached. The clutch enables high- precision tightening torques (+/- 15% in flexible fastenings and +/- 10% in rigid fastenings), increases productivity and eliminates waiting times. The system prevents vibration of the operator’s hand. The clutch range is adjusted using one of the variety of springs available. Screwdrivers of the ACCU-TRK® family are supplied with a clutch spring enabling use of the maximum torque. If you require a lower adjustment range, request a spring with a lower rating.

Technical specification

Model	ERGOVIT20AT
Code	8302311
No-load speed - rpm/min	1800
Screw tightening - Metal	M4 - M5
Torque - Nm	1,8-3,5
Spring colour	Orange
Length - mm	221
Body - ø mm	41
Air connection	1/4”GAS
Weight - Kg	0,9
Hose - ø min mm	8
Air consumption - Nl/min	420

Screwdrivers with torque control - Clutch type: ACCU-TRK

Data sheet
ERGOVIT20AT

GUN SCREWDRIVERS - Button /push start - ERGOVIT series
WATT: 220
Hexagonal coupling: 1/4”

Overall dimensions

